

YY-7306

Micro ATX Slim Desktop Case







Compact

11.35L

Screw-less

Designed with quick fasteners, make system assembly easy and quick

Standard

Allow standard size devices

Cable planning

The reserved cable tunnel may hide cable mess and promote the efficiency of system assembly and thermal ability

Quiet/Optimum Thermal Efficiency

- All new Air Flow Design Partition air guide, more efficiency, not only for Core area, but also for devices and add-on-cards
- Not only for Core 2 Duo(65W) today, but also for Quad Core generation (95W) tomorrow

SPECIFICATIONS

| Case dimension | 333mm W x 355mm D x 96mm H | |
|------------------------------|--|---------------------------|
| (without bezel) | 13.1"W x 13.9"D x 3.8"H | |
| Motherboard configuration | Micro ATX, DTX | |
| Drive configuration | 4 drive bays: 1 - 5.25" expos | sed |
| | 1 - 3.5" expo | sed |
| | 2 - 3.5" hidde | en |
| Optional system cooling fans | 1 * 8015mm DC fan for front-mounted | |
| Expansion slots and ports | 4 slots | |
| Front panel control | Power switch, Power LED, HDD LED | |
| | USB2.0*2+ HD AUDIO+USB3.0*2 (Option) | |
| Materials | Recyclable materials; Steel chassis | |
| | Flame retardant plastic parts and front bezel(HB) | |
| Emissions | Designed to meet FCC class B-47 CFR part15/IEC/CISPR 22:1993 | |
| Color | Black Chassis /Silver Bezel or Titanium Bezel | |
| Power Supply | TFX 250W~300W | |
| Options | 1x8015mm fan, Foot Stand, Intrusion Switch, Multi-in-one Card Reader, Internal Speaker + Amp PCB kits | |
| Net Weight | 3.2kgs/7.04lbs | |
| Shipping/Packing | 0.95cuf't/Single packed carton | 60pcs/honeycomb box(bulk) |
| | 1070pcs/20'container | 1360pcs/20'container |
| | 2160pcs/40'container | 3000pcs/40' container |
| | 2500pcs/40'HQ container | 3120pcs/40'HQ container |